

PD792 Ex

Intrinsically Safe Digital Portable Radio



- ATEX / IECEx / FM / CSA / CQST IIC Certificated
- Designed for Hazardous Working Environments





PD792 Ex

Two-way radios have been a productivity tool for many professionals. For those who work in environments with explosive gas and combustible dusts using standard radios could be unsafe.

We understand what the challenges are for professionals working in hazardous environments. Dedicated to the designing and delivering of innovative intrinsically safe communications solutions, We launched PD792 Ex, a portable DMR radio that complies with the world's strictest safety standards.

Applications

Oil & Gas

Utilities

Mining

Manufacturing

Firefighters

Refineries

Pharmaceutical




Product Features

- Environmentally Safe and High Reliability**
 The PD792 Ex is designed upon the strict requirements of European ATEX and North American FM standards. With certifications for ATEX, IECEx, the latest FM and CSA specifications, the radio works safely in most hazardous environments, even with the presence of hydrogen and dust particles. The overall design complies with the latest American Military Standard-MIL-STD-810G, which means it can bear the harshest environments like High/Low Temperature, High Humidity, Vibration, and Shock.
- Enhanced Safety**
 The PD792 Ex provides a dedicated emergency button. In case of any accident, a press on the button will trigger an alarm and initiate a pre-programmed voice call. Built-in Man-down, GPS and Lone Worker functions are also available with the digital portable.
- High-capacity and Safe Li-Ion Battery**
 The PD792 Ex has a high-capacity Li-Ion battery of 1800mAh with long shelf life of 17 hours under 5-5-90 duty cycle. The battery charging and discharging circuits are stringently designed to prevent overcharging or discharging causing high heat, which leads to unstable battery environments. In addition the battery cells are also encapsulated to redistribute single point heat buildup and also prevent air discharge.
- High Audio Quality and Assured Communication Based on DMR Technology**
 Benefitted from the advantages of DMR digital technology, PD792 Ex provides higher audio quality and stable communication performance with 40% less battery consumption than analog radios. It provides better communication quality and enhanced privacy, and moreover reduces overall equipment costs.
- Easy to Use**
 The PD792 Ex is very easy to use. It has a tough and highly readable LCD screen and an intuitive user interface. The large PPT button and channel knobs are useful for users wearing gloves. The ergonomic design and channel annunciation enhance the user experience.

Technical Highlights

- Improved PCB Circuit Layout & EMC Shielding**
 To achieve such a high safety standard, Hytera PD792 Ex adopts optimized distributed line design on PCB, minimizing the odds of circuit fault. All the key components on the PCB are covered with shield, and the space between lines, between components, between component and shield are properly separated which translates to better EMC performance and less internal interference.
- Innovative Silicone Encapsulating**
 Silicone encapsulant technology prevents the internal circuits from interface with air and liquid which effectively stops the intrusion of liquid, dust and harmful gas. The silicone encapsulating process is delicate and complicated. As a result, every single PD792 Ex radio spends eight hours in the manufacture line.
- Innovative Electrostatic Free Design**
 Hytera applies patent on electrostatic free design and dual-material molding technology in this intrinsically safe portable. The static dispersive material (blue) minimizes static accumulation on the surface, thus reducing the probability of static discharge on the radio. Meanwhile the robust material (black) maximizes the ruggedness of the enclosure.
- IP67 Protection**
 The Ingress Protection reaches IP67 (6: Totally protected against dust; 7: Protected against the effects of immersion up to 1m for 30 minutes). It's the highest IP level for land-based wireless radio application.



Accessories

- Included**
- Li-Ion Battery
 - MCU Rapid-rate Charger
 - Power Adapter
 - Antenna
 - Belt Clip
 - Leather Strap

See website for full list

Optional



Intrinsic Safe Remote Speaker Microphone (IP67)
SM18N4-Ex



Carrying Case with (Leather)(Swivel)
LCY005



Programming Cable (USB Port) PC38



Ex earset with On-Mic PTT
EHN12-Ex

Specifications

General	Frequency range	UHF: 400 - 470MHz VHF: 136 - 174MHz		
	Channel Capacity	1024		
	Zone Capacity	64 (each with maximum of 16 channels)		
	Channel Spacing	12.5 / 20 / 25KHz		
	Operating Voltage	7.4V (rated)		
	Battery	1800mAh (Li-Ion)		
	Battery Life (5-5-90 Duty Cycle, High TX Power) High-capacity 1800mAh Li-Ion Battery	Analog	Approx. 14.5hrs / 13hrs (GPS)	
		Digital	Approx. 17hrs / 15hrs (GPS)	
	Frequency Stability	±1.5ppm		
	Antenna Impedance	50 Ω		
	Dimensions (with standard battery w/o antenna) (HxWxD)	5.55 x 2.16 x 1.53 inches		
	Weight (with standard battery and antenna)	1.1 lbs		
	LCD Display	160 x 128 Pixels, 65,536 Color, 1.8 inches, 4 rows		
Anti-explosion levels	ATEX	II 2G Ex ib IIC T4 ; II 2D Ex ib IIIC T248°F IP5X ; I M2 Ex ib		
	IECEX	Ex ib IIC T4 ; Ex ib IIIC T248°F IP5X ; Ex ib I		
	FM	Class I, Zone 1 Aex ib IIC T4 Gb ; Class II, III Div 1 ; Group E, F, G T248°F ; -4°F ≤Ta ≤122°F		
Environmental Specifications	Operating Temperature	-4°F ~ +122°F		
	Storage Temperature	-40°F ~ +185°F		
	ESD	IEC 61000 - 4 - 2 (level 4) ±8kV(contact) ±15kV (air)		
	American Military Standard	MIL-STD-810 C/D/E/F/G		
	Dust & Water Intrusion	IP67 Standard (non-explosive-proof)		
	Humidity	Per MIL-STD-810 C/D/E/F/G Standard		
	Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard		
GPS	TTFF (Time To First Fix) Cold Start	<1 minute		
	TTFF (Time To First Fix) Hot Start	<10 seconds		
	Horizontal Accuracy	<10 meters		

Transmitter	RF Power Output	1W (adjustable)	
	FM Modulation	11KφF3E @ 12.5KHz; 14KφF3E @ 20KHz; 16KφF3E @ 25KHz	
	4FSK Digital Modulation	12.5KHz Data Only: 7K6φFXD 12.5KHz Data & Voice: 7K6φFXW	
	Conducted/Radiated Emission	-36dBm<1GHz; -30dBm>1GHz	
	Modulation Limiting	± 2.5KHz @ 12.5KHz; ±4.0KHz @ 20KHz; ± 5.0KHz @ 25KHz	
	FM Hum & Noise	40dB @ 12.5KHz; 43dB @ 20KHz; 45dB @ 25KHz	
	Adjacent Channel Power	60dB @ 12.5KHz; 70dB @ 20/25KHz	
	Audio Response	+1 ~ -3dB	
	Audio Distortion	≤ 3%	
	Digital Vocoder Type	AMBE++ or SELP	
Digital Protocol	ETSI-TS102 361-1, 2&3		

Receiver	Sensitivity	Analog	0.3 μ V (12dB SINAD) ; 0.22V μ (typical) (12dB SINAD); 0.4 μ V (20dB SINAD)
		Digital	0.3 μ V/BER5%
	Selectivity TIA-603 ETSI	60dB @ 12.5KHz / 70dB @ 20/25KHz 60dB @ 12.5KHz / 70dB @ 20/25KHz	
	Intermodulation TIA-603 ETSI	70dB @ 12.5/20/25KHz 65dB @ 12.5/20/25KHz	
	Spurious Response Rejection TIA-603 ETSI	80dB @ 12.5/20/25KHz 84dB @ 12.5/20/25KHz	
	Hum & Noise	40dB @ 12.5KHz; 43dB @ 20KHz; 45dB @ 25KHz	
	Rated Audio Power Output	0.5W	
	Rated Audio Distortion	≤3%	
Audio Response	+1 ~ -3dB		
Conducted Spurious Emission	< -57dBm		



Hytera America

Address: 3315 Commerce Parkway
Miramar, Florida 33025, USA
Tel: 800-845-1230 Fax: 954-846-1672
http://www.hytera.us
Stock Code: 002583.SZ

Hytera reserves the right to change product designs or specifications at any time. If you have any questions regarding the accuracy of this information please contact your local sales representative or Hytera directly.

HYT, Hytera are registered trademarks of Hytera Co., Ltd. © 2013 Hytera Co., Ltd. All rights reserved.

EN20131028A