

TC610

Professional Analog Portable Radio

Ideal for outdoor use because of its water & dust protection, IP66 rating makes it extremely useful for jobs that may encounter wet & dirty environments and allows for the radio to be washed after use in a dirty / dusty environment. The unique easy-grip design helps prevent dropping, the patented battery latch design keeps the battery from separating from the radio if dropping does occur.



Highlights

- **Unique Easy-Grip Design**
Provides increased security against dropping.
- **Patented Battery Latch**
This latch prevents separation of the battery and the radio if dropped.
- **Long Battery Life**
2000mAh high capacity Li-Ion battery lasts approximately 14hrs.
- **IP66 Protection**
The Ingress Protection reaches IP66 (6: Totally protected against dust; 6: Protected against the effects of streaming water (12.5 mm nozzle) from any direction).
- **Voice Operated Transmit (VOX)**
Hands-free transmit is possible, when paired with a compatible accessory.
- **Discrete Version**
An all black version is available when using for discrete applications such as Casinos, Funeral Escorts, Security, and Hotels.

Features

- High / Low Power Switchable
- Programmable Channel Spacing (Wide / Narrow Band Selectable)
- LED Battery Gauge
- TX Admit
- ATIS
- CTCSS / CDCSS Encode & Decode
- Channel Scan
- Auto Battery Save
- Low Battery Alert
- Data Operated Squelch
- Selectable Squelch Level (0-9)
- Time-out-timer (TOT)
- PC Programmable
- Wired Clone

Applications

Construction



Manufacturing



Warehouse

Hotel



Port

Events

Property Management



Accessories

Included

- Li-Ion Battery
- MCU Charger
- Power Supply
- Antenna
- Belt Clip
- Strap

Optional

See website for full list



D-Earpiece with In-Line MIC, PTT, & VOX EHM15



MCU Rapid-rate Charger (for Li-Ion/Ni-MH Battery) MCA02



Programming Cable (USB Port) PC26



Nylon Carrying Case (Non-Swivel)(Black) NCN001

Specifications

General	Frequency Range	VHF: 136-174 MHz ; UHF1: 400 - 420MHz ; UHF2: 450-470MHz
	Channel Capacity	16
	Channel Spacing	25 / 12.5KHz
	PLL Channel Stepping	5 kHz, 6.25 kHz
	Operating Voltage	7.4V
	RF Power Output	VHF: High 5W - Low 2W UHF: High 4W - Low 2W
	Battery	2000mAh (Li-Ion)
	Battery Life (5-5-90 Duty Cycle,	Approx. 14hrs
	Frequency Stability	± 2.5ppm
	Operating Temperature	-4° F ~ 131° F
	Antenna Impedance	50 Ω
	Dimensions (HxWxD)	4.68 x 2.16 x 1.30 Inches
	Weight	9.7oz
	FCC ID	See website for full list
	Canada Industry ID	See website for full list



Your Local Dealer

Hytera reserves the right to change product designs or specifications at any time. If you have any questions regarding the accuracy of this information please contact your local sales representative or Hytera directly.

HYT, Hytera are registered trademarks of Hytera Co., Ltd. © 2014 Hytera Co., Ltd. All rights reserved.



Hytera America

Address: 3315 Commerce Parkway
Miramar, Florida 33025, USA
Tel: 800-845-1230 **Fax:** 954-846-1672
http: //www.hytera.us
Stock Code: 002583.SZ

Hytera
Respond & Achieve

EN20140305A